

STONESHORT 180

Apparecchio

Corpo e cornice in alluminio pressofuso (EN 47100). Verniciatura a polvere poliesteri in doppio strato stabilizzata ai raggi UV, resistente alla corrosione e alle nebbie saline.

Guarnizioni in gomma siliconica.

Viteria esterna in acciaio inox AISI 316.

Driver protetto alle sovra-tensioni di rete.

Lenti LED in PMMA.

Schermo in vetro stampato, temperato resistente agli shock termici.

Carico statico sopportabile: 3000-4000Kg.

Apparecchio carrabile alla velocità massima di 20Km/h.

Apparecchio costruito in conformità alle norme

EN 60598-1 e EN 60598-2-13.

Sorgente

LED con efficienza nominale sino a 110lumen/Watt (4000K - 500mA - CRI>80 - Tj=85°C).

Lunga vita utile del LED: > 50000h con L80.

Alta consistenza dei colori: <3 SDCM.

Disponibili versioni con lampade tradizionali.

Installazione

Installazione ad incasso.

Pressacavo PG11 in tecnopolimero.

Controcassa in tecnopolimero.

Questi apparecchi sono predisposti per i moderni sistemi di controllo. Per le diverse possibilità vedi la sezione "Controllo della luce".

Altri colori LED disponibili su richiesta.

Luminaire

Die-cast aluminium body and trim (EN 47100).

Double layer polyester powder paint resistant to corrosion and salt spray fog.

Silicone rubber gaskets.

AISI 316 stainless steel external screws.

Driver protected against voltage surges.

PMMA lenses for LEDs.

Screen made of molded thermal-shock resistant tempered glass.

3000-4000Kg static load capacity.

Can be driven over at maximum speed 20Km/h.

It complies with standards EN 60598-1 and EN 60598-2-13.

Source

Nominal LED efficacy up to 110lumen/Watt

(4000K - 500mA - CRI>80 - Tj=85°C).

LED life time: >50000h with L80.

High colour consistency: <3 SDCM.

Available with conventional lamps.

Installation

Recessed installation.

PG11 engineering plastic cable gland.

Recessed installation box made of engineering plastic.

These fittings are suitable for the modern control systems. For the various possibilities, please see section "Controlling the light".

Different LED colours available upon request.



Accessori, vedi pag. 275.
Accessories, see page 275.

cornice in alluminio pressofuso > die-cast aluminium frame


16 ● 21 ●

Code	WATT	CEI	Class	Lumen sorgente Source lumen	Lumen apparecchio Luminaire lumen	LED	K	CRI	Tmax (°C)	Kg
06890	6W LED	●	⊕	670	100	●	3000	80	39	1,77
06891	6W LED	●	⊕	720	110	●	4000	80	39	1,77
06869	6W LED	●	⊕	720	110	●	5000	80	39	1,77

radente bidirezionale > two-way grazing illumination



Driver LED incluso.
LED driver included.



cornice in alluminio pressofuso > die-cast aluminium frame


16 ● 21 ●

Code	WATT	CEI	Class	Lumen sorgente Source lumen	Lumen apparecchio Luminaire lumen	LED	K	CRI	Tmax (°C)	Kg
06892	6W LED	●	⊕	670	110	●	3000	80	39	1,73
06893	6W LED	●	⊕	720	120	●	4000	80	39	1,73
06870	6W LED	●	⊕	720	120	●	5000	80	39	1,73

radente unidirezionale > one-way grazing illumination



Driver LED incluso.
LED driver included.



cornice in alluminio pressofuso > die-cast aluminium frame


16 ● 21 ●

Code	WATT	CEI	Class	Lumen sorgente Source lumen	Lumen apparecchio Luminaire lumen	LED	K	CRI	Tmax (°C)	Kg
06894	6W LED	●	⊕	670	200	●	3000	80	39	1,65
06895	6W LED	●	⊕	720	220	●	4000	80	39	1,65
06871	6W LED	●	⊕	720	220	●	5000	80	39	1,65

radente radiale > radial grazing illumination



Driver LED incluso.
LED driver included.




cornice in alluminio pressofuso > die-cast aluminium frame

16 ● 21 ●



unidirezionale > one-way illumination

Code	WATT	€	Class	Lumen sorgente Source lumen	Lumen apparecchio Luminaire lumen	LAMP	K	CRI	Tmax (°C)	Kg
07726	1x 10W FSQ G24 d-1	●	⊕	600	●	4000	80	40	40	1,87




cornice in alluminio pressofuso > die-cast aluminium frame

16 ● 21 ●



radiale > radial illumination

Code	WATT	€	Class	Lumen sorgente Source lumen	Lumen apparecchio Luminaire lumen	LAMP	K	CRI	Tmax (°C)	Kg
07728	1x 10W FSQ G24 d-1	●	⊕	600	●	4000	80	40	40	1,74



accessori > accessories

Per poter predisporre in anticipo l'installazione, è possibile ordinare separatamente la controcassa da interrare. L'apparecchio potrà essere ordinato successivamente, e verrà comunque fornito completo di controcassa (da eliminare se acquistato separatamente in precedenza).

*It is possible to purchase the recessed box separately, whenever it is necessary to start the installation in advance.
The item can be ordered later on, and it will be supplied complete with recessed box (to be removed if purchased separately in advance).*



Code	Kg
07795	● 0,20

Controcassa da interrare in materiale termoplastico.
Thermoplastic material recessed installation box.



Code	Kg
07932	● 0,05

Scatola di connessione IP68.
Junction box IP68.

Ø 6,5 - 10 mm

