

# TULA

arcluce.it 🔍 tula



**APPARECCHIO**

- Corpo in alluminio pressofuso.
- Verniciatura a polvere poliesteri in doppio strato stabilizzata ai raggi UV, resistente alla corrosione e alle nebbie saline.
- Guarnizioni in gomma siliconica.
- Viteria esterna in acciaio inox AISI 316.
- Lenti LED in PMMA.
- Schermo in policarbonato opale.
- Apparecchio costruito in conformità alle norme EN 60598-1 e EN 60598-2-1.

**SORGENTE**

- LED con efficienza nominale sino a 142lumen/Watt (4000K - 350mA - CRI>70 - T<sub>j</sub>=85°C).
- Lunga vita utile del LED: >50000h con L80.

**INSTALLAZIONE**

- Installazione a parete.
- Passacavo stagno per entrata singola del cavo di alimentazione.

**LUMINAIRE**

- Die-cast aluminium body.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.
- PMMA lenses for LEDs.
- Opal polycarbonate screen.
- It complies with standards EN 60598-1 and EN 60598-2-1.

**SOURCE**

- Nominal LED efficacy up to 142lumen/Watt (4000K - 350mA - CRI>70 - T<sub>j</sub>=85°C).
- LED life time: >50000h with L80.

**INSTALLATION**







- Wall mounted.
- Waterproof grommet for single cable entry.



Schermo in PMMA per versione con fascio ellittico 7°x66°.  
PMMA screen for 7°x66° elliptical beam.



Schermo a filo per evitare l'accumulo di polvere.  
Flush, smooth screen to reduce dust collection on the surface.



# TULA

Unidirezionale - One-way illumination

arcluce.it  tula


**Schermo in PMMA.**  
PMMA screen.

11  31



Code	WATT	CE	Source lumen	Luminaire lumen	K	CRI	Class
<b>P7210</b>	4W LED	*	520	200	3000	70	⊕
<b>P7211</b>	4W LED	*	560	210	4000	70	⊕
<b>P7212</b>	4W LED	*	560	210	5000	70	⊕

IP66



Driver LED incluso.  
LED driver included.

Bidirezionale - Two-way illumination

**Schermo in PMMA e in vetro.**  
PMMA and glass screen.


11



Code	WATT	CE	Source lumen	Luminaire lumen	K	CRI	Class
<b>P7250</b>	4W + 3W LED	*	520+360	200+80	3000	70+80	⊕
<b>P7251</b>	4W + 3W LED	*	560+390	210+90	4000	70+80	⊕
<b>P7252</b>	4W + 3W LED	*	560+390	210+90	5000	70+80	⊕

<b>P7256</b>	4W + 3W LED	*	520+360	200+80	3000	70+80	⊕
<b>P7257</b>	4W + 3W LED	*	560+390	210+90	4000	70+80	⊕
<b>P7258</b>	4W + 3W LED	*	560+390	210+90	5000	70+80	⊕

IP66



Driver LED incluso.  
LED driver included.


**Schermo in PMMA.**  
PMMA screen.

11



Code	WATT	CE	Source lumen	Luminaire lumen	K	CRI	Class
<b>P7253</b>	4W + 4W LED	*	2x520	2x200	3000	70	⊕
<b>P7254</b>	4W + 4W LED	*	2x560	2x210	4000	70	⊕
<b>P7255</b>	4W + 4W LED	*	2x560	2x210	5000	70	⊕

IP66



Driver LED incluso.  
LED driver included.

