

# ORION


orion



Arcluce Code **0232002A-930-11**

Ex Code

Code EAN **8054378413919**



## Technical information

<b>Light source:</b>	LED, 3000K
<b>Luminaire efficacy:</b>	95lm/W
<b>Luminaire:</b>	5W , 475lm
<b>LED life time:</b>	> 50000h - L80 - B20 (Ta 25°C)
<b>High colour consistency:</b>	< 3 SDCM
<b>Power supply:</b>	220-240V 50/60Hz
<b>Wiring:</b>	ON/OFF
<b>Optics:</b>	flood 36°
<b>Color:</b>	White - 11
<b>Weight:</b>	0.41 kg
<b>Size:</b>	A: Ø 60mm B: 60mm

CE

IP20



## Appliance

- Turned aluminium body and frame.
- Polyester powder paint resistant to UV rays.
- Lenses for LEDs made of optical technopolymer.
- Long LED life time > 50000h.

## Installation

- Suspended installation.
- Base plate made of painted steel.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-1.



# ORION

orion

Arcluce Code **0232002A-930-11**

Ex Code

Code EAN **8054378413919**



## Specifications

With its soft lines and unique design, ORION is the pendant luminaire that offers high-performance optics. The aluminium spherical body envelops the globe of light from the optical technopolymer LED lens, ensuring high visual comfort.

Turned aluminium body and frame. Polyester powder paint resistant to UV rays. Lenses for LEDs made of optical technopolymer. Long LED life time > 50000h.

It complies with standards EN 60598-1 and EN 60598-2-1.

LED sources available in color temperatures 3000K

High color consistency < 3 SDCM and LED life time > 50000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 95lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Suspended installation. Base plate made of painted steel.

Brand ARCLUCE mod. ORION