

# RIGO31


performance



Arcluce Code **0213056A-930-11**

Ex Code

Code EAN **8054378375651**



## Technical information

**Light source:** LED, 3000K, CRI>90

**Indirect light source:** LED, 3000K

**Luminaire efficacy:** 117lm/W

**Luminaire:** 51W , 5950lm

**LED life time:** > 60000h - L80 - B20 (Ta 25°C)

**High colour consistency:** < 3 SDCM

**Power supply:** 220-240V 50/60Hz

**Wiring:** ON/OFF

**Optics:** elliptic 110°x85°

**Indirect Optic:** ultra wide flood 100°

**Color:** White - 11

**Weight:** 3.24 kg

**Size:**  
A: 36mm  
B: 92mm  
C: 1137mm





## Appliance

- Extruded aluminium body.
- End caps made of die-cast aluminium with magnetic fixing.
- Polyester powder paint resistant to UV rays.
- Transparent microprismatic polycarbonate or opal screen.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Suspended installation.
- Steel cable 1.5m for suspension.
- Cable cup with transparent power cable included.

## Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- END CAPS AND SUSPENSION KIT INCLUDED.

## Norm

- It complies with standards EN 60598-1 and EN 60598-2-2.



# RIGO31

performance

Arcluce Code **0213056A-930-11**

Ex Code

Code EAN **8054378375651**



## Specifications

The suspended downlight for decorative lighting

Extruded aluminium body. End caps made of die-cast aluminium with magnetic fixing. Polyester powder paint resistant to UV rays. Transparent microprismatic polycarbonate or opal screen. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-2.

LED sources available in color temperatures 3000K, 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 117lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Suspended installation. Steel cable 1.5m for suspension. Cable cup with transparent power cable included.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. RIGO31