

RIGO51


comfort



Arcluce Code **0211085A-930-11**

Ex Code

Code EAN **8054378374456**



Technical information

Light source: LED, 3000K, CRI>90

Indirect light source: LED, 3000K, CRI>90

Luminaire efficacy: 116lm/W

Luminaire: 40W , 4650lm

LED life time: > 60000h - L80 - B20 (Ta 25°C)

High colour consistency: < 3 SDCM

Power supply: 220-240V 50/60Hz

Wiring: ON/OFF

Optics: extra wide flood 110°

Indirect Optic: extra wide flood 108°

UGR: <19

Color: White - 11

Weight: 3.98 kg

Size:
A: 52mm
B: 110mm
C: 1137mm

CE

IP20



Appliance

- Extruded aluminium body.
- End caps made of die-cast aluminium with magnetic fixing.
- Polyester powder paint resistant to UV rays.
- Transparent microprismatic polycarbonate or opal screen, or reflector in brushed aluminium.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Suspended installation.
- Steel cable 1.5m for suspension.
- Cable cup with transparent power cable included.

Note

- Available versions with Casambi and other modern control systems, for more information see "Light controls" section.
- END CAPS AND SUSPENSION KIT INCLUDED.

Norm

- It complies with standards EN 60598-1 and EN 60598-2-2.



RIGO51

comfort

Arcluce Code **0211085A-930-11**

Ex Code

Code EAN **8054378374456**



Specifications

In the suspended version, RIGO51 is an elegant and functional design detail, able to decorate rooms with its elegance and enhance the environments with the high quality of its light. Featuring a wide versatility of use, it is an ideal solution for numerous interior lighting contexts with a particular vocation for environments featuring a modern interior design, where diffused lighting is at the complete service of people wellness; it is also perfect in functional lighting contexts, when light is used to mark volumes and delimit spaces.

Extruded aluminium body. End caps made of die-cast aluminium with magnetic fixing. Polyester powder paint resistant to UV rays. Transparent microprismatic polycarbonate or opal screen, or reflector in brushed aluminium. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

It complies with standards EN 60598-1 and EN 60598-2-2.

LED sources available in color temperatures 3000K, 3000K

High color consistency < 3 SDCM and LED life time > 60000h - L80 - B20 (Ta 25°C).

System effectiveness, minimum 116lm/W

Luminaire in insulation class I.

DRIVER INCLUDED.

Suspended installation. Steel cable 1.5m for suspension. Cable cup with transparent power cable included.

Available versions with Casambi and other modern control systems, for more information see "Light controls" section.

Brand ARCLUCE mod. RIGO51